



NOTES:

A) STANDARD LENGTHS:
 16-1/2" OLSON #127CG165
 24" OLSON #127CG24

B) TAPPED HOLES IN TOP FLANGE RING ARE LOCATED ON CENTERLINE OF OPENINGS.
 TOLERANCE: $\pm 3/16"$

C) OPENINGS LOCATED 180 DEGREES APART.
 TOLERANCE: ± 1 DEGREE.
 OPTIONAL HOLE SIZES AND/OR LOCATIONS MUST BE SPECIFIED WHEN ORDERING.

E) PLYWOOD COVER FOR L-867 IS 1/2" THICK GRADE CC WITH 7/16" DIA. BOLT HOLES.
 NOTE: PLYWOOD THICKNESS RUNS UNDERSIZE 1/2" - ACTUAL 15/32 +0/-1/32"

A GALVANIZED STEEL COVER (3/4" THICK MAXIMUM), PURCHASED SEPARATELY, MAY BE SUBSTITUTED FOR PLYWOOD COVER.

F) OPTIONAL STEEL LUG FOR GROUNDING PROVISION AND/OR DRAIN COUPLING OR WEEP HOLE MUST BE SPECIFIED WHEN ORDERING.

G) FINISH IS HOT DIP GALVANIZE, ASTM A386 C1.A.

H) (6) 3/8-16" X 1" STAINLESS STEEL HEX HEAD BOLTS SHIPPED WITH L-867 LIGHT BASE.

GROUND LUG	EGL		IGL				
PLYWOOD THICKNESS	STD.		OTHER				
ANTI-ROTATION FINS	#		HT./LOCATION				
DRAIN HOLE & TYPE	SIZE					OTHER	
OPENING LOCATION		0'	90'	180'	270'		
OPENING SIZE	STD 2"						
	OTHER						
STACKED	#						
OPENING HT. ****	STD						
STD. -2-1/2" FROM BTM	OTHER						

UD 06/10/02	DRAWN BY: TOJ/VR	TITLE: L-867 LIGHT BASE - 12" DIA.	OLSON INDUSTRIES, INC. ATKINSON, NE 68713
	APPR. BY: TOJ	MAT. SPEC.: A - 36 MIN.	
	DATE: 09/08/1996	NEXT ASSEM. IS: -----	
	SCALE: 8:1	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	
	FILE NAME: 127CG24	FRACTIONS $\pm 1/32"$ DECIMALS $\pm 0.030"$ ANGLES ± 0.5 Deg.	
			PKG. NO.: 2.0
			MODEL NO.: 127CG
			PART NO.: SEE NOTE A