



NOTES:

- A) "X" = HEIGHT TO ORDER.
- B) FINISH IS HOT DIP GALVANIZE, ASTM A386 C1.A.
- C) (6) 3/8-16 X 1" STAINLESS STEEL BOLTS SHIPPED WITH L-867 EXTENSION.
- D) PLYWOOD COVER FOR L-867 EXTENSION IS 1/2" THICK GRADE CC WITH 7/16" DIA. BOLT HOLES.
- F) L-867 12" NOM. O.D. : OLSON #127E(X) (X=HEIGHT TO ORDER)
 L-867 16" NOM. O.D. : OLSON #167E(X) (X=HEIGHT TO ORDER)
 L-867 24" NOM. O.D. : OLSON #247E(X) (X=HEIGHT TO ORDER)
 L-867 24" NOM. O.D. : OLSON #247EW(X) (X=HEIGHT TO ORDER)
 EX. : 2-1/8" HT. - 127E02125

	NOM. DIA.	"AA"	"BB"	"CC"	"DD"	"X" MIN.
L-867B	12"	10.250	12.375	8.000	13.500	1.750
L-867D	16"	14.250	16.250	12.375	17.375	1.750
L-867E	24"	14.250	23.125	12.375	24	1.750
L-867EW	24"	21.500	23.125	20.000	24	1.750

24" UD 10/21/00 24" UD 5/28/02	DRAWN BY: TLK	TITLE: L-867 EXTENSION - 1-3/4" AND OVER	OLSON INDUSTRIES, INC. ATKINSON, NE 68713	
	APPR. BY: TOJ	MAT. SPEC.: -----		
	DATE: 08/07/1997	NEXT ASSEM. IS: -----		PKG. NO.: 9.0
	SCALE: 8:1	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		MODEL NO.: 7E
	FILE NAME: 12767E	FRACTIONS ± 1/32" DECIMALS ± 0.030" ANGLES ± 0.5 Deg.		PART NO.: SEE NOTE F ABOVE