



(2) 2-3/4" DIA. OPENINGS FOR 2" CONDUIT GROMMETS STD. - OPTIONAL SIZES AND/OR LOCATIONS MUST BE SPECIFIED WHEN ORDERING.

GROUND LUG	EGL	IGL				
PLYWOOD THICKNESS	STD.	OTHER				
ANTI-ROTATION FINS	#	HT./ LOCATION				
DRAIN HOLE & TYPE	SIZE				OTHER	
OPENING LOCATION		0'	90'	180'	270'	
OPENING SIZE	STD 2"					
	OTHER					
STACKED	#					
OPENING HT. ****	STD					
STD. -2-1/2" FROM BTM	OTHER					

A) OPENINGS LOCATED 180 DEGREES APART.
TOLERANCE: +/- 1 DEGREE.

B) PLYWOOD SHIPPING COVER FOR L-868 BOTTOM SECTION IS 3/4" THICK GRADE CC. 5/8" THICK TYPICAL WHEN USED WITH MUD PLATE.

C) (6) 3/8-16 X 1" STAINLESS STEEL BOLTS SHIPPED WITH L-868 BOTTOM SECTION.

D) FINISH IS HOT DIP GALVANIZE, ASTM A386 C1.A.

E) OPTIONAL EQUIPMENT: STEEL LUG FOR GROUND PROVISION, DRAIN COUPLING OR OPENING MUST BE SPECIFIED WHEN ORDERING.

F) L-868 10" NOM. O.D. : OLSON #108BSG125
L-868 12" NOM. O.D. : OLSON #128BSG125
L-868 15" NOM. O.D. : OLSON #158BSG125
OPTIONAL HEIGHTS: EX. 128BSG155
HEIGHT = 15.5"

	NOM. DIA.	"AA"	"BB"	"CC"	"DD"	"EE"	OPTIONAL "EE" FOR CONCRETE CASEMENT *
L-868	10"	10.000	8.250	6.000	10.375	10.375	12.375 OLSON #108BSGW125
L-868	12"	12.000	10.250	9.250	12.375	12.375	13.500 OLSON #128BSGW125
L-868	15"	15.000	13.250	12.375	15.375	15.375	17.375 OLSON #158BSGW125

* MUST BE SPECIFIED WHEN ORDERING.

Updated 5/10/02
Updated 1/03/03

DATE:	10/06/96	TITLE:	L-868 BOTTOM SECTION 10",12",15" DIA.	OLSON INDUSTRIES
SCALE:	1/8"=1"	MAT. SPEC:		East Hwy 20, Atkinson, NE 68713
DRAWN BY:	TLK	UNLESS OTHERWISE NOTED, DIMENSIONS ARE IN INCHES		PACKAGE NO.: 11.1
APPROVED:	TOJ	FRACTIONS +/-	DECIMALS +/-	ANGLES +/-
FILE NAME:	128158BSG.CAD			MODEL NO.: 8BSG
				PART NO.: SEE NOTE F ABOVE