

MWC REAR LOAD CONTAINER SPECIFICATIONS									
	1 YD	1 1/2 YD	2 YD	2 YD SLOPE	3 YD	4 YD w/casters	4 YD - std. w/o casters	6 YD	8 YD
TOP WIDTH	63"	60 1/2"	63"	63"	63"	63"	63"	63"	63"
BOTTOM WIDTH	60"	50 1/4"	60"	60"	60"	60"	60"	60"	60"
SIDES (ga.) *	14 ga.	14 ga.	14 ga.	14 ga.	14 ga.	12 ga.	12 ga.	12 ga.	12 ga.
BOTTOM (ga.) *	14 ga.	14 ga.	14 ga.	14 ga.	14 ga.	12 ga.	12 ga.	10 ga.	10 ga.
TOP DEPTH	27"	34"	40 1/2"	44 1/2"	72"	90"	83"	119"	154"
BOTTOM DEPTH	17 1/4"	28"	36 1/2"	28 3/4"	46 1/2"	60"	48"	60"	110"
HEIGHT	37"	41"	40 3/4"	40 3/4"	40"	40"	46"	46 1/2"	46 1/2"
TOP FRAME MATERIAL	3/16"x1.5"SQ TUBE	3/16"x1.5"SQ TUBE	3/16"x1.5"SQ TUBE	3/16"x1.5"SQ TUBE	3/16"x1.5"SQ TUBE	3/16"x1.5"SQ TUBE	3/16"x1.5"SQ TUBE	11ga x1.5x3" TUBE	3/16" x1.5x3" TUBE
REAR TOP FRAME DOUBLED **	NO	NO	NO	NO	NO	3/16"x1.5"SQ TUBE	3/16"x1.5"SQ TUBE	11ga x1.5x3" TUBE	3/16" x1.5x3" TUBE
TRUNION SHAFT SIZE	1 1/4"	1 1/4"	1 1/4"	1 1/4"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"
NO. LIDS	2	2	2	2	4	4	4	6	8
DISTANCE FROM GND TO CENTER OF TRUNION BAR	49"	49"	49"	49"	48-1/4"	48-1/4"	47-1/4"	48"	48"
NOTE: 3, 4, 6, & 8 yd. containers use combination of one universal lid. Four swivel casters std. on 1 thru 3 yd. containers.									
* Optional 12 ga. sides/bottoms available on 2 & 3 yd. containers.									
** Rear top frame is reinforced with a 2nd member.									
Distance between gusset and end washer on trunion bar equals 3".									
Length of trunion bar including end washers equals 77-1/2".									

Rear Load Container Features:

All sizes stackable.

Poly lids custom made to our specifications. No right or lefts.

Steel lids optional. Same lid fits 3 through 8 yd. allowing for easier maintenance and lower inventory.

Rubber caster wheels for ease in rolling.

Easy replacement of casters - No bolts.

Four swivel casters standard. Greasable.

Square/rectangular tubing top frame for better container structural integrity and increased life.

100% inside body welding. - Longer container life.